

Commercial Refrigeration Recovery/Recycling Equipment Certified for Performance Characteristics in Accordance with the United States Clean Air Act

COMPANY
APPION INC

2800 S Tejon St

Englewood, CO 80110-1208 United States

SA13136

Certified for performance in accordance with EPA's Minimum Requirements for Recycling or Recovery Equipment.

Performance Data

Model Dsg	Refrigerant	Liquid Recovery Rate (kg/min)	Vapor Recovery Rate (kg/min)	Final Recovery Vacuum Level kPa	High Temp (104 F) Vapor Recovery Rate (kg/Min)
<i>G5 TWIN</i>	R22	4.7	0.28	50.53	0.27/0.28(++)
	R134A	3.7/4.6(+)	0.20/0.21(++)	50.53	—
	R407C	5.41	0.25	50.53	—
	R410A	7.8	0.25	50.53	—
<i>G1 SINGLE</i>	R22	3.88	0.12	50.53	0.14
	R134A	2.36	0.10	50.53	—
	R407C	2.65	0.14	50.53	—
	R410A	1.96	0.12	50.53	—

(+) - Using high speed direct liquid procedure - Inline cooling procedure per the unit operating manual.

(++) - Vapor rate obtained using the optional cooling coil accessory.